

# 4. Tire Changers



## TIRE CHANGER

KE -2092T



- Semi-auto
- Double helper arms

KE-2370T



- Full automatic
- Pneumatic operated tilting column
- Equipped with tubeless tire inflating device

### Specification

Model	KE-2092T	KE-2370T	KE-2030T	KE-2090T
Motor power	0.75kw/0.55kw/1.1kw	0.75kw/0.55kw/1.1kw	0.75kw/0.55kw/1.1kw	0.75kw/0.55kw/1.1kw
Power supply	220V/110V	220V/110V	220V/110V	220V/110V
Max. wheel diameter	45"(1143mm)	45"(1143mm)	45"(1143mm)	45"(1143mm)
Max. wheel width	16"(406mm)	16"(406mm)	16"(406mm)	16"(406mm)
Outside clamping	12"-23"	12"-23"	12"-23"	12"-23"
Inside clamping	14"-26"	14"-26"	14"-26"	14"-26"
Air supply	8bar	8bar	8bar	8bar
Bead breaker force	2500kg	2500kg	2500kg	2500kg
Noise level	<75dB	<75dB	<75dB	<75dB
Weight	303/266kg	445/395kg	238/210kg	300/268kg
Package size	1130x900x1030mm	1550x310x550mm	1130x900x1030mm	1130x900x1030mm

KE -2030T



KE-2090T



The manufacture reserves the right to change the product specifications without notice and liability in order to upgrade the quality.

For Motor bike KE-2406T / Truck, Bus KE-2614T, KE-5614T

Motorcycle

KE-2406T



Specification

Model	KE -2406T
Motor power	0.75kw/0.55kw/1.1kw
Power supply	220V/400V/110V
Max. wheel diameter	41"(1040mm)
Max. wheel width	14"(355mm)
Clamping	6"-24"
Air supply	8bar
Bead breaker force	2500kg
Noise level	<75dB
Weight	195/171kg
Package size	960x760x930mm

- Humanization designed mounting & demounting head special for motorcycle
- Adjustable clamp suitable for motorcycle

TRUCK, BUS

KE-2614T



KE-4214T



KE-5614T



Specification

- Bus, truck
- Clockwise and anticlockwise rotation of the clamp range from 14"-56"
- Automatic electro hydraulic operation
- Movable controlling unit
- Hydraulic motor with pressure adjustment device
- Automatic fast turning
- Wireless Remote control unit(Optional)

Specification

Model	KE -2614T	KE-4214T	KE-5614T
Pump motor	1.5kw, 380V, 3PH	2.2kw, 380V, 3PH	2.4/3.0kw
Rotating motor	1.8kw, 380V, 3PH	2.2kw, 380V, 3PH	2.4/3.0kw
Clamping capacity	14"-26"	14"-42"	14"-56"
Max. tire diameter	1600mm	2300mm	2500mm
Max. tire width	780mm	1050mm	1200mm
Max. tire weight	500kg	1600kg	2200kg
Weight	570/647kg	758/850kg	980/860kg
Package size	2030x1600x1000mm	2130x1850x1090mm	2330x2110x1100mm

The manufacture reserves the right to change the product specifications without notice and liability in order to upgrade the quality.