DIGITAL BATTERY TESTER / BATTERY CHARGER / SPARK PLUG TESTER / ARMATURE TESTER







Analogue

DBT-1000C

DBT-600

BT-200

Specification						
Model	DBT-1000C	DBT-600	BT-200			
Testing voltage	DC 10 ~ 40V	DC 8 ~ 16V	DC 0 ~ 16V			
Testing Bettery / Capacity	12V, 24V	Ah	Ah			
Applicable contents	Battery Capacity, Life of span, Internal Resistance, CCA, AH, DIN, IEC, EN	Battery status, Condition of alternator & generator, Accidental short circuitry in wiring				
Dimension	115 × 230 × 95mm	320 × 200 × 250mm	330 × 220 × 225mm			
Weight	3.5 Kg	4.6 Kg	7 Kg			



MAX-60D



SPCT-100



111111111111111111111111111111111111111		0.0.100		7	
Specification					
Model	MAX-60D	Model	SPCT-100	Model	AT-11
Description	Bettery Charger & Load Tester	Description	Spark Plug Tester	Description	Armature Tester
Input Voltage	Single phase 110/220V,	Input voltage	Single phase 220V	Power	220V, 50/60Hz
	50/60Hz, 4.5KVA	Frequency	50 ~ 60Hz	AC Ampere	2A
Output Voltage	DC 12/ 24V	The working	7 ~ 10KG/cm²	Checking Voltage	24V
Rectification	SCR type	pressure of air		Application	40 ~ 120mm
Dimension	260(W)mm x 450(L)mm x 670(H)mm	The quantity of sand for working	350 g	checking range	
Weight	about 58kg		60.#	Weight	6.6 Kg
	ŭ .	The particle of sand	60 #	Dimension	160 x 190 x 250mm
Insulation type	A Type double insulation	The voltage of tester when spark testing	15,000V	Features (AT-11)	
Safety Devicev	Overheating sensor, Automatic stop function			,) ner armature's core, armature's coil,
		Dimension	490(W)×280(L)×265(H) mm	and commutator is regularly insulated through testing armature earth. It can check the short circuit of armature core's intervals. It can check whether the segments of circuit broke by using the test leader.	
Main Power Code	2.5M / 2.5M	Weight	9.3 Kg		
Remarks	Change up to 8pcs auto battery of a passenger car	Accessory	Adapter for plug 12mm, 14mm each 2pcs, Adapter case 1pcs, Spare sand 350g		
			Spare Sariu Soug	It can test the armature with ampere meter.	

	AT-11
	AT-11
otion	Armature Tester
	220V, 50/60Hz
pere	2A
ng Voltage	24V
ation ng range	40 ~ 120mm

- armature's core, armature's coil, gularly insulated through testing
- circuit of armature core's
- It can test the armature with ampere meter.

Features (MAX-60D)

- It can test formed voltage of generator.It is used to check accidental short-circuit.
- It is designed to simultaneously check the specific gravity of battery liquid and starting capacity of automobile battery.

Features (SPCT-100)

- ${\boldsymbol{\cdot}}\,$ It can completely remove carbon from spark plug owing to blows the minute abrasive particle by high pressure air.

 It can check the ignition of spark plug have their best conditions.
- · It can also automatically clean the spark plug.

The manufacture reserves the right to change the product specifications without notice and liability in order to upgrade the quality.